


Mat, Inc.
FLOODWOOD, MINNESOTA



S P

SPECTACK

SOIL SOLUTIONS

Spectack is an organic tackifier (dispersable Polysaccharide) manufactured in the USA and is specifically designed for use as a hydraulically applied erosion control tackifier. **Spectack** is used as a standalone temporary erosion control product with wood, paper, or other native fiber mulches to provide superior bonding strength. **Spectack** is specially designed to develop optimal slurry viscosity to improve sprayability and pump performance. **Spectack** disperses in water creating a lump free slurry, saving time and money.

Recommended Application Rates:

It is recommended that **Spectack** be applied at 10 to 25 lbs. per 1000 gallons of water depending on machines capacity. When used as an overspray for straw, use Spectack more concentrated at the rate of 40 lbs. to 1000 gallons of water per acre with the use of 150 to 300 lbs. of mulch as a marker.

<u>SLOPE:</u>	Flat	4:1	3:1	2:1
<u>LBS/ACRE:</u>	30-80	50-100	80-120	100-170

Safe Handling and Use:

Precaution: Inhaling dust may irritate lungs and/or cause allergic responses in some individuals. Use caution as material will become slippery on wet deck surfaces. Store unused quantities in a cool, dry place. Not a plant food product.


Mixing Instructions:

1. Add water to tank to cover blades of lower agitator.
2. Add Spectack slowly while filling tank with agitator at high speed.
3. After Spectack is thoroughly mixed, add mulch, seed and fertilizer.

For More Information call: 1-888-477-3028 Fax: 1-218-476-2039

Net. Wt. 40 lbs. (4-10 lbs. bags)

Mat, Inc.
FLOODWOOD, MINNESOTA



S P

SPECTACK

SOIL SOLUTIONS

Spectack is an organic tackifier (dispersable Polysaccharide) manufactured in the USA and is specifically designed for use as a hydraulically applied erosion control tackifier. **Spectack** is used as a standalone temporary erosion control product with wood, paper, or other native fiber mulches to provide superior bonding strength. **Spectack** is specially designed to develop optimal slurry viscosity to improve sprayability and pump performance. **Spectack** disperses in water creating a lump free slurry, saving time and money.

Recommended Application Rates:

It is recommended that **Spectack** be applied at 10 to 25 lbs. per 1000 gallons of water depending on machines capacity. When used as an overspray for straw, use Spectack more concentrated at the rate of 40 lbs. to 1000 gallons of water per acre with the use of 150 to 300 lbs. of mulch as a marker.

<u>SLOPE:</u>	Flat	4:1	3:1	2:1
<u>LBS/ACRE:</u>	30-80	50-100	80-120	100-170

Safe Handling and Use:

Precaution: Inhaling dust may irritate lungs and/or cause allergic responses in some individuals. Use caution as material will become slippery on wet deck surfaces. Store unused quantities in a cool, dry place. Not a plant food product.


Mixing Instructions:

1. Add water to tank to cover blades of lower agitator.
2. Add Spectack slowly while filling tank with agitator at high speed.
3. After Spectack is thoroughly mixed, add mulch, seed and fertilizer.

For More Information call: 1-888-477-3028 Fax: 1-218-476-2039

Net. Wt. 40 lbs. (4-10 lbs. bags)

Mat, Inc.
FLOODWOOD, MINNESOTA



S P

SPECTACK

SOIL SOLUTIONS

Spectack is an organic tackifier (dispersable Polysaccharide) manufactured in the USA and is specifically designed for use as a hydraulically applied erosion control tackifier. **Spectack** is used as a standalone temporary erosion control product with wood, paper, or other native fiber mulches to provide superior bonding strength. **Spectack** is specially designed to develop optimal slurry viscosity to improve sprayability and pump performance. **Spectack** disperses in water creating a lump free slurry, saving time and money.

Recommended Application Rates:

It is recommended that **Spectack** be applied at 10 to 25 lbs. per 1000 gallons of water depending on machines capacity. When used as an overspray for straw, use Spectack more concentrated at the rate of 40 lbs. to 1000 gallons of water per acre with the use of 150 to 300 lbs. of mulch as a marker.

<u>SLOPE:</u>	Flat	4:1	3:1	2:1
<u>LBS/ACRE:</u>	30-80	50-100	80-120	100-170

Safe Handling and Use:

Precaution: Inhaling dust may irritate lungs and/or cause allergic responses in some individuals. Use caution as material will become slippery on wet deck surfaces. Store unused quantities in a cool, dry place. Not a plant food product.


Mixing Instructions:

1. Add water to tank to cover blades of lower agitator.
2. Add Spectack slowly while filling tank with agitator at high speed.
3. After Spectack is thoroughly mixed, add mulch, seed and fertilizer.

For More Information call: 1-888-477-3028 Fax: 1-218-476-2039

Net. Wt. 20 lbs.

Mat, Inc.
FLOODWOOD, MINNESOTA



S P

SPECTACK

SOIL SOLUTIONS

Spectack is an organic tackifier (dispersable Polysaccharide) manufactured in the USA and is specifically designed for use as a hydraulically applied erosion control tackifier. **Spectack** is used as a standalone temporary erosion control product with wood, paper, or other native fiber mulches to provide superior bonding strength. **Spectack** is specially designed to develop optimal slurry viscosity to improve sprayability and pump performance. **Spectack** disperses in water creating a lump free slurry, saving time and money.

Recommended Application Rates:

It is recommended that **Spectack** be applied at 10 to 25 lbs. per 1000 gallons of water depending on machines capacity. When used as an overspray for straw, use Spectack more concentrated at the rate of 40 lbs. to 1000 gallons of water per acre with the use of 150 to 300 lbs. of mulch as a marker.

<u>SLOPE:</u>	Flat	4:1	3:1	2:1
<u>LBS/ACRE:</u>	30-80	50-100	80-120	100-170

Safe Handling and Use:

Precaution: Inhaling dust may irritate lungs and/or cause allergic responses in some individuals. Use caution as material will become slippery on wet deck surfaces. Store unused quantities in a cool, dry place. Not a plant food product.

Mixing Instructions:

1. Add water to tank to cover blades of lower agitator.
2. Add Spectack slowly while filling tank with agitator at high speed.
3. After Spectack is thoroughly mixed, add mulch, seed and fertilizer.

For More Information call: 1-888-477-3028 Fax: 1-218-476-2039

Net. Wt. 20 lbs.